

# AH-0218

## Fire Alarm Bell 6"



# AH-9718

## Fire Alarm Bell 4"

# AH-9719

## Fire Indicating Lamp



### AH-0218 Features

- High efficiency low current consumption on 24VDC motorized bells.
- Terminals will accept 2.5mm cables.
- Simple installation via multi-fixing base plate for all types of location.
- Fitted with two series diodes for fault monitoring.
- Option of customized discs printed with company name and logo.
- 12VDC bells are also available.

### AH-9718 Features

- Motor energized, low power consumption (28mA), long operating life.
- Bell shell is made of steel plate, so it will sound loud and clear.
- 220VAC bells are also available.

### AH-9719 Features

- Uses white bulb (or low current LED) and installed inside the red lamp cover.
- When lit, it is clear visible within 10 meters.

Approvals: EN54



Approvals: CNS

Approvals: CE

### Specification

Model	AH-0218	AH-9718	AH-9719
Dimensions	ø6" (152mm) x 56mm(H)	ø4" (100mm) x 50mm(H)	90mm(Dia.) x 70mm(H)
Voltage	24V DC	-	-
Current	25mA	-	-
Consumption Current	-	24V DC 28mA	24V DC 60mA / LED 20mA
Energize Type	-	Motor	-
Sound Output	93dB @1M	90dB/M and above	-
Movement	Motor, Pinion and striker	-	-
Movement Features	DC Motor, acetal gear wheel, steel striker	-	-
Gong	Steel, secured with phillips screw	-	-
Base Plate	Molded black polycarbonate	-	-
Material	-	Steel plate	-
Bulb	-	-	30V/2W white bulb or LED
Lamp Cover	-	-	Fire-proof plastic
Lamp Base	-	-	Fire-proof plastic
Weight	About 850g	About 450g	About 70g